CLAIMS:

We claim:

2

3

4

5

6

2

3

1

2

1

1 1. A database access system comprising:

a universal database connectivity driver having a first exposed interface through which access to a database server can be provided;

a database proxy driver registered with said universal database connectivity driver, said database proxy driver having a second exposed interface which conforms with said first exposed interface of said universal database connectivity driver, said database proxy driver having a configuration for invoking at least one auxiliary task in addition to providing access to said database server through said first exposed interface of said universal database connectivity driver; and,

a database driven application programmatically linked to said database proxy driver.

- 2. The database access system of claim 1, wherein each of said universal database connectivity driver, database proxy driver and database driven application are disposed in an edge device in a computer communications network.
- 3. The database access system of claim 2, wherein said auxiliary task is load balancing.
 - 4. The database access system of claim 1, wherein said auxiliary task is caching.

The line

1

2

1

2

- 5. The database access system of claim 1, further comprising:
- a log file of data request meta-information; and,
- an application analyzer configured to tune operation of said auxiliary task based
- 4 upon said meta-information.
 - 6. A database access method, the method comprising:
 - receiving a database connectivity request through a corresponding first exposed database connectivity method from a database driven application;

forwarding said database connectivity request to an underlying database connectivity driver through a corresponding second exposed method having a method prototype which matches a method prototype of said first exposed database connectivity method; and,

performing at least one auxiliary task in addition to forwarding said database connectivity request.

- 7. The database access method of claim 6, further comprising performing each of the receiving, forwarding and performing steps in an edge device.
- 1 8. The database access method of claim 7, wherein said performing step 2 comprises performing a load balancing task.
- 1 9. The database access method of claim 7, wherein said performing step comprises performing a database caching task.

The special state of

2

3

4

5

6

7

1

- 1 10. The database access method of claim 6, further comprising:
 2 collecting meta-data for each received database connectivity request; and,
 3 modifying operation of said auxiliary task based upon an analysis of said
 4 collected meta-data.
 - 11. The database access method of claim 10, wherein said modifying step comprises generating rules which direct database connectivity requests to particular instances of a database server which are most likely to respond quickly based upon database latency patterns inherent in said collected meta-data.
 - 12. The database access method of claim 11, wherein said modifying step comprises selectively caching result sets in a database cache based upon request frequency patterns inherent in said collected meta-data.
 - 13. A machine readable storage having stored thereon a computer program for providing database access, the computer program comprising a routine set of instructions for causing the machine to perform the steps of:
 - receiving a database connectivity request through a corresponding first exposed database connectivity method from a database driven application;
 - forwarding said database connectivity request to an underlying database connectivity driver through a corresponding second exposed method having a method

2

3

4

8

9

10

11

2

prototype which matches a method prototype of said first exposed database connectivity method; and,

performing at least one auxiliary task in addition to forwarding said database connectivity request.

- The machine readable storage of claim 13, further comprising performing each of 14. 1 : the receiving, forwarding and performing steps in an edge device.
 - The machine readable storage of claim 14, wherein said performing step 15. comprises performing a load balancing task.
 - The machine readable storage of claim 14, wherein said performing step 16. comprises performing a database caching task.
 - The machine readable storage of claim 13, further comprising: 17. collecting meta-data for each received database connectivity request; and, modifying operation of said auxiliary task based upon an analysis of said collected meta-data.
- The machine readable storage of claim 17, wherein said modifying step 18. 1 comprises generating rules which direct database connectivity requests to particular 2 instances of a database server which are most likely to respond quickly based upon 3 database latency patterns inherent in said collected meta-data. 4

- 1 19. The machine readable storage access method of claim 17, wherein said
- 2 modifying step comprises selectively caching result sets in a database cache based
- 3 upon request frequency patterns inherent in said collected meta-data.